



D10 UNIVERSAL THINNER NORMAL

Regular thinner for Acrylics

A) DESCRIPTION AND FIELDS OF APPLICATION:

Especially formulated to obtain a great reduction in viscosity. Promotes better flow and prevents blushing. Its balanced evaporation insures perfect base and finishing coats.

B) TECHNICAL DATA:

Composition	Ester and ketone base solvents
Specific weight	0,872 ± 0,03 kg/l
Available colours	Colourless
Safety data	See safety data sheet

C) PROCESSING :

For metalized solvent base coats, 2K acrylic and polyurethane finishes.

For 2K acrylic and polyurethane primer-surfacers.

Mixing ratio : Add from 5% to 100% depending on the required viscosity.

D) CAUTIONS:

* Utilize at room temperatures below 25°C.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A.

42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42124 Reggio Emilia - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42124 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384

Stabilimento: 26817 S. Martino in Strada (LO) - Via del Commercio, 1 - Tel. +39 0371 475313 - Fax +39 0371 475370

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357